

W1**“Normal” Mini-clip****Zinc-plated mild steel****“Normal” Mini-clip W1**

Information	d Ø Application mm	Reference W1	r	e	a	b	s	Max. values* Torque Nm	Max. values* Pressure (Bars)	Box Quantity	Packing
The use of malleable mild steel in the manufacture of the “Normal” mini-clip means that when tightened, the clip adapts perfectly to the hose, clamping firmly but gently. This clip is recommended for use with gaseous fluids at low pressure.	6	03010510	M3	5	8,4	9	0,5	0,4	15,0	100	1600
	8	03010528	M3	5	9	9	0,5	0,4	14,0	100	1600
	9	03010536	M4	6	10	10	0,5	1,0	15,0	100	1600
	9,5-10	03010544	M4	6	10	10	0,5	1,0	14,0	100	1600
	10-11	03010552	M4	6	10	10	0,5	1,0	13,0	100	1600
	12-13	03010560	M4	6	10	10	0,5	1,0	12,5	100	1600
	13-14	03010579	M4	6	10	10	0,5	1,0	12,5	100	1600
	14-15	03010587	M4	6	10	10	0,5	1,0	12,0	100	1600
	15-17	03010595	M4	6	10	10	0,5	1,0	12,0	100	1600
	16-18	03010608	M4	6	10	10	0,5	1,0	11,5	100	1600
	18-20	03010616	M4	6	10	10	0,5	1,0	10,5	100	1600
	19-21	03010624	M4	6	10	10	0,5	1,0	10,5	100	800
	20-22	03010632	M4	6	10	10	0,5	1,0	10,5	100	800
	22-25	03010640	M4	6	10	10	0,5	1,0	9,5	100	800
	23-26	03010659	M4	6	10	10	0,5	1,0	9,0	100	800
	25-28	03010667	M4	6	10	10	0,5	1,0	8,5	100	800
26-29	03010675	M4	6	10	10	0,5	1,0	8,5	100	800	
29-32	03010683	M4	6	10	10	0,5	1,0	8,0	100	800	

* The maximum pressure may vary depending on the type of hose and coupling used

W1 Materials**Screw:**

6.6 strength
Grey-white Cr3 zinc-plated

Nut:

6 strength
White Cr3 zinc-plated

Band:

St 02Z (DIN 1.0226)

